

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



The Delphion
Integrated
View

Other Views:
INPADOC

Title: **JP2001107809A2: GAS FUEL INTERNAL COMBUSTION ENGINE**

Country: JP Japan

Kind: A2 Document Laid open to Public inspection

Inventor(s): **NAKAJIMA YASUO
YAMANE KIMITAKA**

Applicant/Assignee: **GOTO IKUEIKAI**
[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: April 17, 2001 / Oct. 6, 1999

Application Number: JP1999000284977

IPC Class: **F02M 21/02; F02D 19/02; F02D 41/04; F02D 41/08; F02D 41/34;
F02D 43/00; F02F 3/26; F02P 5/15;**

Priority Number(s): Oct. 6, 1999 JP1999000284977

Abstract:

Problem to be solved: To provide a spark ignition type natural gas internal combustion engine provided with no throttle valve and control a load by an injection amount and to improve fuel consumption in a low load area.


Solution: This internal combustion engine comprises a main fuel injection valve 11 to inject natural gas in the cavity combustion chamber 14 of a piston 7; an auxiliary fuel injection valve 12 to inject natural gas to an ignition chamber 9; and an ignition plug 10 situated at the ignition chamber 9. Since, during idling, fuel is fed only from the auxiliary injection valve 12 and ignited and burnt in the ignition chamber 9, stable operation at a high excess air factor is practicable. At a partial load area, fuel is injected from the main fuel injection valve 11, and before fuel is excessively diffused in a cavity combustion chamber 14, flame generated due to combustion in the ignition chamber 9 is injected through a communication hole 13 for ignition and combustion. At a total load area, fuel is injected from the main fuel injection valve 11 in the vicinity of a bottom dead center and brought into a state approximately equal to premixture.

COPYRIGHT: (C)2001,JPO

Family: [Show known family members](#)

Other Abstract Info: none

Foreign References: No patents reference this one



[View Image](#)

1 page



Nominate
this for the
Gallery



(19)

(11) Publication number:

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 11284977

(51) Intl. Cl.: F02M 21/02 F02D 19/02 F02D 41/04
41/34 F02D 43/00 F02F 3/26 F02P 5/1

(22) Application date: 06.10.99

(30) Priority:

(43) Date of application publication: 17.04.01

(84) Designated contracting states:

(71) Applicant: GOTO IKUEIKAI

(72) Inventor: NAKAJIMA YASUO
YAMANE KIMITAKA

(74) Representative:


(54) GAS FUEL INTERNAL COMBUSTION ENGINE

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a spark ignition type natural gas internal combustion engine provided with no throttle valve and control a load by an injection amount and to improve fuel consumption in a low load area.

SOLUTION: This internal combustion engine comprises a main fuel injection valve 11 to inject natural gas in the cavity combustion chamber 14 of a piston 7; an auxiliary fuel injection valve 12 to inject natural gas to an ignition chamber 9; and an ignition plug 10 situated at the ignition chamber 9. Since, during idling, fuel is fed only from the auxiliary injection valve 12 and ignited and burnt in the ignition chamber 9, stable operation at a high excess air factor is practicable. At a partial load area, fuel is injected from the main fuel injection valve 11, and before fuel is excessively diffused in a cavity combustion chamber 14, flame generated due to combustion in the ignition chamber 9 is injected through a communication hole 13 for ignition and combustion. At a total load area, fuel is injected from the main fuel injection valve 11 in the vicinity of a bottom dead center and brought into a state approximately equal to premixture.

COPYRIGHT: (C)2001,JPO



L1 ANSWER 2 OF 2 CAPLUS COPYRIGHT 2002 ACS
 AN 2001:269852 CAPLUS
 TI Gas fuel internal combustion engine. [Machine Translation].
 IN Nakajima, Yasuo; Yamane, Kimitaka
 PA [NAME NOT TRANSLATED], Japan
 SO Japan Kokai Tokkyo Koho, 7 pp.
 CODEN: JKXXAF
 DT Patent
 LA Japanese
 FAN.CNT 1

| | PATENT NO. | KIND | DATE | APPLICATION NO. | DATE |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|----------|-----------------|----------|
| PI | JP 2001107809 | A2 | 20010417 | JP 1999-284977 | 19991006 |
| AB | [Machine Translation of Descriptors]. The throttle valve ingredient preparation do, offers the natural gas internal combustion engine of the high tension ignition formula which can control load at the injection quantity, fuel economy of low load limits improves. Facing to inside cavity combustion room 14 of piston, 7 possesses with the spark plug 10 which is provided in the secondary fuel injection valve 12 which injects the natural gas to the main fuel injection valve 11 which injects the natural gas and ignition room 9 and ignition room 9. When idling, from only secondary fuel injection valve 12 the fuel to be supplied, because ignites burns inside ignition room 9, driving which at high excess air factor stabilizes is possible. In partial load limits, the fuel is injected first from main fuel injection valve 11, inside cavity combustion room 14 excessively to the former which the diffusion is done, the flame by the combustion inside ignition room 9 gushes from communication hole, 13 ignites burns. In full load limits, near bottom dead center the fuel is injected from main fuel injection valve, 11 becomes a state where is close to premixing. | | | | |
| IC | ICM F02M021-02 ICS F02M021-02; F02D019-02; F02D041-04; F02D041-08; F02D041-34; F02D043-00; F02F003-26; F02P005-15 | | | | |

| | SINCE FILE ENTRY | TOTAL SESSION |
|--------------------------------------------|------------------|---------------|
| => log y COST IN U.S. DOLLARS | 27.49 | 27.70 |
| FULL ESTIMATED COST | | |
| DISCOUNT AMOUNTS (FOR QUALIFYING ACCOUNTS) | SINCE FILE ENTRY | TOTAL SESSION |
| CA SUBSCRIBER PRICE | -1.24 | -1.24 |

STN INTERNATIONAL LOGOFF AT 13:10:37 ON 10 JUN 2002